



DETECTABLE & NON-DETECTABLE TAPE



PRODUCT SPECIFICATIONS

DETECTABLE MARKING TAPE

- Detectable Marking tape consists of a minimum 5.0Mil overall thickness, with a (0.00035") solid aluminum foil core. Construction is 0.8 Mil clear film, reverse printed and laminated to aluminum foil laminated to 3.75 Mil clear film, making the film permanently printed.
- The tape meets or exceeds industry standards including the American Public Works Association (APWA) color code.
- Detectable tape is available in 2", 3", 6" and 12" widths and applications include:
 - * Red Caution Buried Electric Line
 - * Orange Caution Buried Fiber Optic Line
 - * Brown Caution Buried Force Main
 - * Green Caution Buried Force Main
 - * Yellow Caution Buried Gas Line
 - * Orange Caution Oil Line
 - * Purple Caution Buried Reclaimed Water Line
 - * Green Caution Buried Sewer Line
 - * Green Caution Buried Storm Drain
 - * Orange Caution Buried Telephone Line
 - * Blue Caution Buried Water Line

NON-DETECTABLE MARKING TAPE

- Non-detectable marking tape consists of a 4.0 Mil overall thickness. It is manufactured with no lead material and is used for underground purposes.
- Super stretch Non-Detectable marking tape consists of a minimum 6.0 Mil overall thickness, is reverse printed and has a laminated construction for prolonged use underground.
- Both Detectable and Non-Detectable tape meets or exceeds industry standards including the American Public Works Association (APWA) color code.
- Available in different widths.

BARRICADE TAPE

Yellow Barricade tape consists of a 4.0 Mil overall thickness and is offered in 3" Width weather resistant poly with easy to read 2" black lettering such as:

- CAUTION
- DANGER
- CAUTION DO NOT ENTER
- QUARANTINE
- And Many More

Available in Domestic & Import