



TNE MEC[®] 140-1211 PRIMER COATED C110 DUCTILE IRON FLANGED FITTINGS

TNE MEC[®] 140-1211 PRIMER COATED C110 DUCTILE IRON FLANGED FITTINGS

BASIC SPECIFICATIONS

- SIZES:** • 2" - 64"
- MATERIAL:** • Ductile Iron ASTM A536 Grade 60-42-10, 65-45-12 or 70-50-05.
- PRESSURE:** • 250 PSI Water Working Pressure for Ductile Iron sizes 2" - 48".
• 150 PSI Water Working Pressure for Ductile Iron sizes 54" - 64".
- TESTING:** • In accordance with ANSI / AWWA C110 / A21.10 where applicable.
• Other items are in accordance with manufacturer's standards.
• 54" and above Flanged Fittings are manufactured as per AWWA C153/A21.53.
• All fittings are hydrostatically tested in accordance with SIGMA Quality Management Standard.
• All fittings are heat coded to ensure traceability and verification of metallurgical properties in accordance with SIGMA Quality Management Standards.
- LAYING LENGTH:** • In accordance with ANSI / AWWA C110 / A21.10 where applicable.
• Other items are in accordance with manufacturer's standards.
• 54" and above Flanged Fittings are manufactured as per AWWA C153/A21.53.
- COATING:** • **TNE MEC[®] Series N140 Pota-Pox[®] Plus** Innovative potable water coating which offers high-build edge protection and allows for application at a wide range of temperatures (down to 35°F or 2°C with 44-700 Accelerator). For use on the interior and exterior of steel or concrete tanks, reservoirs, pipes, valves, pumps and equipment in potable water service.
- GASKETS:** • SBR in accordance with ANSI/AWWA C111/A21.11 & ANSI/AWWA C111/A21.11.
• Also available in EPDM, NBR and CR.
- APPROVALS:** • 2"-16" Underwriters Laboratories listed and Factory Mutual Approved.
- STANDARDS:** • Certified to NSF61 Standard including Annex G & 372.
• ANSI / AWWA C110 / A21.10 Where applicable.
• Other items are in accordance with manufacturer's standards.
• 54" and above Flanged Fittings are manufactured as per AWWA C153/A21.53.
- INSTALLATION:** • Per ANSI/AWWA C600 and C111 using DIP conforming to C150/C151 and PVC pipe conforming to C900/C905.

