



TNE MEC[®] 140-1211 PRIMER COATED C110 DUCTILE IRON PUSH-ON FITTINGS

TNE MEC[®] 140-1211 PRIMER COATED C110 DUCTILE IRON PUSH-ON FITTINGS

BASIC SPECIFICATIONS

- SIZES:**
- 4" - 24"
- MATERIAL:**
- Ductile Iron ASTM A536, Grade 65-45-12, 60-42-10 or 70-50-05.
- PRESSURE:**
- 350 PSI Water Working Pressure 4" - 24"
- TESTING:**
- In accordance with ANSI/AWWA C110/A21.10
 - In accordance with UL - FM requirements.
 - All fittings are hydrostatically tested in accordance with SIGMA Quality Management Standard.
 - All fittings are heat coded to ensure traceability and verification of metallurgical properties in accordance with SIGMA Quality Management Standards.
- LAYING LENGTH:**
- In accordance with ANSI/AWWA C110/A21.10.
- DEFLECTION:**
- Up to 5 degrees, in accordance with TYTON JOINT bell design.
- COATING:**
- **TNE MEC[®] Series N140 Pota-Pox[®] Plus** Innovative potable water coating which offers high-build edge protection and allows for application at a wide range of temperatures (down to 35°F or 2°C with 44-700 Accelerator). For use on the interior and exterior of steel or concrete tanks, reservoirs, pipes, valves, pumps and equipment in potable water service.
- GASKETS:**
- Dual hardness SBR in accordance with ANSI/AWWA C111/A21.11.
 - Also available in EPDM, NBR and CR.
- JOINT:**
- TYTON JOINT design
- APPROVALS:**
- 4"-16" Underwriters Laboratories listed and Factory Mutual Approved.
- STANDARDS:**
- Certified to NSF61 Standard including Annex G & 372.
 - ANSI/AWWA C110/A21.10 for Full Body Ductile Iron Push-On Fittings for water and other liquids.
- INSTALLATION:**
- Per ANSI/AWWA C600 and C111 using DIP conforming to C150/C151 and PVC pipe conforming to C900/C905.

